
FIXED TRACK ROLLING STORAGE – MANUAL ASSIST



Features

- Australian designed, engineered and manufactured
- Units are fully modular and can be easily relocated and extended
- Wide range of Standard sizes – Custom sizes available for individual applications
- Ideal for all floor surface regardless of variable levels
- Integrated Anti-Tilt with fail safe aluminium (not PVC) safety mechanism
- Construction from 1.0mm Zinc Coated high strength steel. Mobile Carriages are fully welded 2.5mm (min) Zinc Steel
The Track is a 50mm x 20mm Bright Steel Bar engineered for heavy duty long term use. Tracks are levelled, packed with non-shrink high impact grout and fixed to the floor during installation
Unit to be provided with waxed Timber EO Board False Floor with 450mm Centre Batten positions with a metal access ramp positioned in-board of the entry side of the Mobile Carriage
- Rolled post construction for strength and not restricted access
- Back panels cover conceal exposed fittings for streamline office aesthetics
- Distributes loads evenly
- Barrel Exchange Master Key System
- Additional locks and CSM storage Pods may be incorporated to provide individual security requirements
- Decorative end dress panels cover the entry side to provide an aesthetically pleasing and contemporary feel.
A decorative end cover panel to the wall side is optional and normally specified where aisle access is required from both sides
- Standard Decorative end panels are made of powder coated steel in a choice over 200+ colours
- Panels may be ordered in the client's choice of perforations, vinyl, laminate or have a mirror finish

Accessories (available separately)

- | | |
|---|--|
| <ul style="list-style-type: none"> • Adjustable Slotted Shelf Dividers • Additional Shelves • Coat Compartments • Roll Out Suspension File Frames • Pull Out Multi Media Drawers | <ul style="list-style-type: none"> • Roll Out Reference Shelf • Paper Management Units • CSM Storage Pods with Tambour Doors • A4 or A5 Card Holders |
|---|--|

Technical Specifications

Drive Type	Push Pull Handle	Bay Heights	2000mm 2200mm 2390mm
Locking Types	Standard Lock Barrel Exchange Master Key System	Bay Widths	700mm 900mm 1050mm 1200mm
End Panel Options	Perforations Laminate Timber Mirrored Graphic Prints	Bay Depths	300mm 425mm 460mm 605mm
Shelves	Shelf heights adjustable in 25mm increments to suit A4 Lever Arch or Lateral Filing Shelf Thickness: 25mm	Weight Loadings	900mm wide bay: 100kg maximum per shelf evenly distributed 1200mm wide bay: 65kg maximum per shelf evenly distributed
Security	Single point locking standard Optional CSM Storage Pods Additional locks may be provided for client requirements to provide security for individual aisles	End Panel Options	Perforations Laminate Timber Mirrored Graphic Prints
Colours	Internal: Off White External: Dulux Powder Coat Colour range (some finishes may attract surcharges)		

* Add 170mm for overall system height

* Add 140mm for overall system width including handle

Please allow an additional 50mm clearance on each bay side for installation purposes to overall unit footprint.

All dimensions are nominal and subject to change without notice. Shelf measurements are based on standard lateral files. Contact CSM to discuss customisable sizes.

Overall Dimensions – Fixed Track Manual (nominal)

